

Creates a traditional exterior finish

Kas-Kel's 300 series new construction rolling windows feature an integrated brickmold trim package, which creates a traditional exterior finish.

The brickmold trim also serves as a J-channel pocket making for a clean finish look and easy installation.

NFRC Thermal Performance Data*

U-VALUE	SHGC	VLT	CR	ZONE
0.25	0.27	0.47	47	N,NC
0.29	0.37	0.52	59	NC
0.29	0.29	0.52	59	NC
0.33	0.29	0.52	56	
0	0	0	-	
	0.25 0.29 0.29 0.33	0.25 0.27 0.29 0.37 0.29 0.29 0.33 0.29	0.25 0.27 0.47 0.29 0.37 0.52 0.29 0.29 0.52 0.33 0.29 0.52	0.25 0.27 0.47 47 0.29 0.37 0.52 59 0.29 0.29 0.52 59 0.33 0.29 0.52 56

^{*}contact us to see thermal data with grids.

KAS-KEL WINDOWS WILL OFFER YOU A LIFETIME OF WORRY-FREE OPERATION, BACKED BY ONE OF THE BEST WARRANTIES IN THE INDUSTRY.









	Features	STANDARD	OPTION
MATERIALS	High-grade PVC delivers exceptional strength and thermal performance. White or beige Interior	Ø	
	Fusion Welded Sash and Frame		
	Removable Sash for cleaning	Ø	
	Fully Weather Stripped Interlock		
	Frame Depth 3 5/8"	<!--</td--><td></td>	
PERF	DP 35 Rating		
	DP 40 Rating		Ø
GLAZING	Energy Star III	Ø	
	Energy Star U-4		Ø
	Clear insulated glass		Ø
	Duralite flexible, warm-edge spacers		
	Tints, Heat Reflection and other options available		Ø
SCREENS	Aluminum Extruded Fiberglass 1/2 screen		
	Aluminum framed fiberglass full screen		Ø
	Full Flexscreens on painted exteriors		Ø
	Aluminum Screening Material		\bigcirc
CONSTRUCTION	Composite Reinforced Meeting Rail		
	Integral Nail Fin	Ø	
	Integral Nail Fin and J-Channel		
	4 9/16" , 6 9/16", and custom Pre-Primed Extension Jamb		Ø
TTS	3/4" Contoured Grill Between the Glass		Ø
GRILLS	3/4" Contoured SDL with spacer bar		Ø
HARDWARE	Masterview Rolling Windows are built on precision-calibrated rollers for long life and smooth fingertip operation.	Ø	
	Cam Locks made to stand up to frequent use.	Ø	
	All windows over 28 inches tall have 2 sash locks for maximum protection	Ø	
	Produced in white or beige to seamlessly match your window frame	Ø	

