

The 300 Double Hung window utilizes an integrated **brickmold trim** package or a 3 ½" vinyl trim option, both of which also serve as a J-channel pocket for easy installation. An elegant, classic look and advanced design with high thermal ratings and glazing package options that meet or exceed Energy Star requirements.

GLAZING	U-VALUE	SHGC	VLT		
Energy Star U4	0.23	0.27	0.48	51	N,NC
Energy Star III	0.27	0.37	0.52	51	NC
Low E w/ Argon	0.27	0.28	0.52	63	NC
High Perf. Low E	0.31	0.28	0.52	63	
Clear	0	0	0	-	

<sup>\*</sup>contact us to see thermal data with grids.

KAS-KEL WINDOWS WILL OFFER YOU A LIFETIME OF WORRY-FREE OPERATION, BACKED BY ONE OF THE BEST WARRANTIES IN THE INDUSTRY.









NSTRUCTION HARDWARE COLOR ON But Wig Ni	on Welded Sash and Frame  ed Sill with Interlocking Leg  8" Frame Depth  35 Rating  50 Rating  rgy Star III  rgy Star U-4 Glass  ble Strength Glass  r insulated glass  alite flexible, warm-edge spacers  5, Heat Reflection and other options available  ninum framed fiberglass full screen		
STRUCTION  HARDWARE  CLEENS  Door  Tinni  Allu  Full  Allu  For winni  Bri  Cor  Na  Door  Door  Door  Tinni  Allu  For winni  Bri  Door	8" Frame Depth 35 Rating 50 Rating rgy Star III rgy Star U-4 Glass ble Strength Glass r insulated glass alite flexible, warm-edge spacers s, Heat Reflection and other options available ninum framed fiberglass full screen		
STRUCTION  HARDWARE  SCREENS  Con  Door  All  Full  All  For Proposition  Brit  Cor  Na  Door  D	35 Rating 50 Rating rgy Star III rgy Star U-4 Glass ble Strength Glass r insulated glass alite flexible, warm-edge spacers s, Heat Reflection and other options available ninum framed fiberglass full screen		
STRUCTION  HARDWARE  SCREENS  Cole  Door  All  Full  All  For Property of the	rgy Star III rgy Star U-4 Glass ble Strength Glass r insulated glass alite flexible, warm-edge spacers s, Heat Reflection and other options available ninum framed fiberglass full screen	<ul><li>♥</li><li>♥</li></ul>	<ul><li>♥</li><li>♥</li><li>♥</li><li>♥</li></ul>
Ene	rgy Star III rgy Star U-4 Glass ble Strength Glass r insulated glass alite flexible, warm-edge spacers s, Heat Reflection and other options available ninum framed fiberglass full screen	<ul><li>✓</li><li>✓</li></ul>	
STRUCTION HARDWARE SCREENS Alu All Full All For Sor Sor Sor Sor Sor Sor Sor Sor Sor S	rgy Star U-4 Glass  ble Strength Glass  r insulated glass  alite flexible, warm-edge spacers  s, Heat Reflection and other options available  ninum framed fiberglass full screen	<ul><li>♥</li><li>♥</li></ul>	<ul><li>Ø</li><li>Ø</li><li>Ø</li></ul>
Clee Dun Trini Alu ALDWARE STRUCTION AIL PARDWARE PROMARE PROM	ble Strength Glass  r insulated glass  alite flexible, warm-edge spacers  s, Heat Reflection and other options available  ninum framed fiberglass full screen	<ul><li>✓</li><li>✓</li></ul>	<ul><li>Ø</li><li>Ø</li><li>Ø</li></ul>
Tint  Alu Alu Alu Alu Alu Alu Alu And	r insulated glass  alite flexible, warm-edge spacers  5, Heat Reflection and other options available  ninum framed fiberglass full screen	<ul><li></li><li></li></ul>	<ul><li>Ø</li><li>Ø</li><li>Ø</li></ul>
Tint  Alu Alu Alu Alu Alu Alu Alu And	alite flexible, warm-edge spacers s, Heat Reflection and other options available ninum framed fiberglass full screen	<ul><li>✓</li><li>✓</li></ul>	<ul><li>♥</li><li>♥</li></ul>
Tint  Alu Alu Alu Alu Alu Alu Alu And	s, Heat Reflection and other options available ninum framed fiberglass full screen	<ul><li></li><li></li></ul>	<b>⊘</b>
Alu Alu ARDWARE SCREENS Alu Alu Arion Ario	ninum framed fiberglass full screen	<b>©</b>	<b>O</b>
STRUCTION  HARDWARE  SCREENS  All  Local Local  But  Country  Na  Door		<b>Ø</b>	<b>O</b>
All v for Nig Nig Nig Pro Non Na Nig Nig Non Na Nig Nig Non Na Nig	ninum framed fiberglass half screen		<b>Ø</b>
All v for Nig Nig Nig Pro Non Na Nig Nig Non Na Nig Nig Non Na Nig			_
All v for Nig Nig Nig Pro Non Na Nig Nig Non Na Nig Nig Non Na Nig	Flex Screen on painted products		<b>Ø</b>
HARDWARE  Nig  No  Cor  Na  Doi	ninum Screening Material		<b>Ø</b>
Bri Con Na	vindows over 23 1/2 inches have 2 sash locks maximum protection	<b>Ø</b>	
Bri Con Na	nt Latches	<b>Ø</b>	
Bri Con Na	CD sash limiters		<b>Ø</b>
Na Doi	duced in white or beige to seamlessly match your dow frame	<b>Ø</b>	
Doi Na	kmold exterior profile	<b>Ø</b>	
Dough Dough	posite Reinforced Meeting Rail	<b>Ø</b>	
J Ch Dou	ling fin with J Channel	<b>⊘</b>	
O J Ch	ble weather stripped Meeting Rail	<b>Ø</b>	
	and the state of t		
Bot	annel Filler		
	0		<b>Ø</b>
3/4	annel Filler		
<b>SHLLS</b> 3/4	annel Filler om and Top Sash Tilt in for easy cleaning ned Solid Pine Applied Extension Jambs		
	annel Filler  om and Top Sash Tilt in for easy cleaning  ned Solid Pine Applied Extension Jambs 16", 6-9/16" and Custom		<b>⊘</b>

