

The 300C Picture window utilizes a New England Style 3 ½" Cambridge Flat Casing which integrates a built -in J-channel pocket for siding and nail-fin for installation. (filler available). An elegant, classic look and advanced design with high thermal ratings and glazing package options that meet or exceed Energy Star requirements. Factory applied off the edge design ensures maximum weather protection.

NFRC Thermal Performance Data*

| | U-VALUE | SHGC | VLT |
|------------------|---------|------|------|
| Energy Star U4 | 0.22 | 0.28 | 0.50 |
| Low E w/ Argon | 0.25 | 0.30 | 0.55 |
| Energy Star III | 0.26 | 0.39 | 0.55 |
| High Perf. Low E | 0.29 | 0.30 | 0.55 |
| Clear | 0.45 | 0.65 | 0.68 |

^{*}contact us to see thermal data with grids.









| | Features | STANDARD | OPTION |
|--------------|---|----------|------------|
| MATERIALS | High-grade PVC delivers exceptional strength and thermal performance. White or beige Interior | ② | |
| | Fusion Welded Sash and Frame | Ø | |
| | Cambridge Flat Casing | Ø | |
| | 3-5/8" Frame Depth | Ø | |
| PERF | DP 50 Rating | Ø | |
| GLAZING | Energy Star III | Ø | |
| | Energy Star U-4 | | Ø |
| | Clear insulated glass (3/4") | | ⊘ |
| | Duralite flexible, warm-edge spacers | | Ø |
| | Tints, Tempered and Double Strength and other options available | | \bigcirc |
| GRILLS | 3/4" Contoured Grill Between the Glass | | |
| | 3/4" Contoured SDL with spacer bar | | Ø |
| CONSTRUCTION | Integral Nail Fin | Ø | |
| | Integral Nail Fin and J-Channel | Ø | |
| | Available without J-Channel | | Ø |
| | 4 9/16", 6 9/16", and custom Pre-Primed Extension Jamb | | |

KAS-KEL WINDOWS OFFER YOU A LIFETIME OF WORRY-FREE OPERATION, BACKED BY ONE OF THE BEST WARRANTIES IN THE INDUSTRY.

